STANDARD BIDDING DOCUMENTS

SUPPLY OF ICT EQUIPMENTS & ACCESSORIES



Samtse College of Education

Samtse, Bhutan

2023



प्र्युगाःकुषायहेवायार्श्वनास्थे

SAMTSE COLLEGE OF EDUCATION



Ref: 37/SCE-Ouot /2023-2024/ 27

Date: 6th July 2023

The General Manager Advertisement Division **Kuensel Corporation** Thimphu.

Sir/Madam,

The undersigned would like to request your office to kindly publish the following notice inviting tender in your newspaper dated 7th July 2023 and bill may be sent to us for payment:

SAMTSE COLLEGE OF EDUCATION NOTICE INVITING TENDER

Samtse College of Education is pleased to invite sealed tender from the eligible license holders for the supply and services of the following items for the financial year 2023-2024.

Sl. No	Particulars	
1	Supply of Stationery items	
2	Supply of Hardware, Electrical & Plumbing items	
3	Supply of Games & Sports items	
4	Supply of IT equipment & Accessories	
5	Supply of Science laboratory equipment & chemical	
6	Supply of Vegetables, Grocery and Meat items	
7	Supply of Library Books	

The bidding documents can be downloaded from our website http://www.sce.edu.bt of Samtse College of Education. The last date for submission of tender is 27th July 2023 at 12:00 PM and it will be opened on the same day at 2:30 PM.

For any further inquiry, please contact Administrative Section at 05-365273, during working hours.

President

Yours sincerely.

(Rinchen Dorji, PhD

PRESIDENT

1	Package	4
2	Quotation	ICT Equipments & Accessories
3	Last date of submission	27 th July, 2023 at 12pm
4	Place of submission	Office of Store In-charge
5	Date of opening	27 th July, 2023 at 2.30pm
6	Place of opening	Conference Hall
7	EMD	Nu. 10,000 (Ten Thousand only)



ICT Equipment's and Accessories 2023-2024

TERMS AND CONDITIONS

- 1. The rates quoted shall be CIF Samtse College of Education for the supply of ICT Equipment & Accessories. Generally, the rates quoted shall be inclusive of all charges/levies/taxes which the suppliers shall bear.
- 2. The quotation should be accompanied by the valid trade license issued by the Ministry of Economic Affairs and the Tax Clearance Certificate issued by the Department of Revenue and Customs, Royal Government of Bhutan, as the enclosure. Quotation without a valid trade license and tax certificate as enclosure shall be rejected.
- 3. The tender shall be accompanied by an application to the PRESIDENT, Samtse College of Education.
- 4. Sealed envelopes containing the quotation shall be marked **Original** and **Duplicate** in separate envelopes. The quotation will be opened in the Conference Hall, Samtse College of Education on 27th July 2023 at 2.30 PM.
- 5. The rates quoted shall be valid for a period of 12 months from the date of quotation.
- 6. Goods should be supplied within 30 days from the date of issue of the purchase order.
- 7. Earnest money of Nu.7500.00 (Seven thousand five Hundred) only should be furnished in the form of Cash Warrant/Bank Draft/Unconditional bank guarantee in favour of the **PRESIDENT**, Samtse College of Education. Quotation without earnest money shall be rejected.
- 8. The College reserves the right to vary the quantity up to 10% on the same terms and conditions.
- 9. All equipment supplied must be as per the specification and any fake item noticed shall be rejected, returned at the supplier's cost and shall be dealt with as per Clause 18 of the terms and conditions.
- 10. The College reserves the right to reject all or any tender without assigning any reason.
- 11. If the supplier fails to supply the required quality and quantity of goods, the College Administration will forfeit the earnest money and terminate the contract without any explanation and the supply order will be given to the next evaluated lowest bidder.
- 12. Failing to submit the quotation within the submission dateline shall be declared as 'late' and rejected. The same would be returned unopened to the supplier.



- 13. The rules and regulations for the establishment and operation of Industrial and Commercial ventures must be adhered to with regard to the establishment of license ventures.
- 14. The rates should be quoted against the specification provided and failing to quote in conformity with the specification shall be disqualified for evaluation.
- 15. The purchaser shall not be responsible for any damage, loss or undue incident that occurred during the transportation. The supplier will be fully responsible for making them good at his own cost.
- 16. The supplier should have a warranty of one year from the date of delivery.
- 17. The supplier should be able to supply the material immediately during the time of emergency and if the bidder fails to supply the required material the bidder shall bear the expenses to purchase from another supplier for the College, Samtse.
- 18. The committee will directly reject the tender if the supplier supplies duplicate/fake or compromised material and the College Administration will forfeit the earnest money and terminate the contract without any explanation and the supply order will be given to the next evaluated lowest bidder.
- 19. If the selected bidder fails to supply the goods within the stipulated time, the liquidated damages of Nu.0.1% per day the bill amount will be imposed.
- 20. Pursuant to the condition above, the second-lowest bidder at his quoted rate shall be asked to supply the goods after submitting performance security to the College Administration.
- 21. The performance security retained with the College shall be refunded to the concerned supplier after the completion of the supply of goods.
- 22. The College will process the bills for payment only upon complete delivery of the goods to the College.
- 23. Decision taken by the College Tender Committee will be final and binding.
- 24. In addition to the terms and conditions mentioned above, all other relevant regulations of the Procurement Manual 2009, shall apply where specific mention is not made.



List of ICT Equipments for 2023-2024

Sl. No	Description of Items	Make/Brand	Unit Price (Nu.)	Remarks
1	Computer Parts & Accessories			
1.1	External SSD 1TB			
1.2	Internal HDD 8 TB			
1.3	USB Mouse (Good Quality)			
1.4	USB Keyboard (Good Quality)			
1.5	Standard VGA Card			
1.6	10GB Dual port PCI-express 2.0x8 Ethernet Expansion Card			
1.7	1GB Dual port PCI-express 2.0x8 Ethernet Expansion Card			
1.8	Standard 10/100/1000Mbps LAN Card			
1.9	VGA Cable 15m			
1.10	HDMI Cable 15m			
1.11	CMOS Battery			
1.12	SMPS for Dell Optiplex 3060/3080			
1.13	SMPS for Dell Precision 3650 Tower			
1.14	USB thumb Drive (8 & 16 GB)			
1.15	HDMI Splitter (One Input and three ore more outputs)			
1.16	VGA Splitter (One Input and three ore more outputs)			
1.17	two side usb Universal Micro USB(5m)			
1.18	HDMI to Mini HDMI Cable 10m for Canon EOS 5D Mark IV Camera			
1.19	Flash For Canon EOS 5D Mark IV Camera (Speedlite or Equivalent)			
1.20	128GB Ultra SDXC UHS-I Memory Card (180 MB/s read speed)			



2	LCP Projector (Epson EB-S42 or Equivalent)		
	Display Type: LCD		
	• Light Output: 2700 Lumens		
	• Warranty: 2 Year(s)		
	• Features: Convenient Connection to a Document Camera, Direct Display		
	from USB, Eco Friendly, HDMI Connectivity, High Contrast Ratio, Horizontal		
	Keystone Adjuster, IR Receivers, Wireless Transmission		
	Audio: Mono		
	• Life of Lamp - Full Usage: 5000 Hours		
	• Life of Lamp - Eco Usage: 6000 Hours		
	• Screen Coverage: 30-350 Inches		
	Contrast Ratio: 10000:1		
	• Throw Ratio: 1.45-1.96		
	• Resolution: SVGA(800x600)		
	Audio Output: 1 Watts		
	Projector Lens: No Optical Zoom-Focus Manual		
3	Projector Lamps		
3.1	EPSON LAMP (EB-S31)		
3.2	EPSON LAMP (EB-S42)		
4	Presenter Remote(Logitec or equivalent)		
5	Printers		
	Features: Auto Duplex Printing		
5.1	Printer Type: Black and White		
0.12	Printing Technology: Laser		
	Print Resolution: 1200x1200 DPI		
5.2	Canon ir2525w or Equivalent		specs attached
6	Back-UPS		
6.1	APC-UPS Backup RS 1100		
7	PowerStrip		
7.1	Universal PowerStrip (15amp) with AC noise filter		
8	Computer repairs and maintenance		
8.1	IP (for wash board)		
8.2	Laptop battery Tester/Charger		
8.3	Laptop Repairing Tools Kits		



8.4	Digital Multimeter (kusum maco)		
8.5	Velleman VTMUS2 Crimping Tool Kit for Network Cables		
8.6	Ethernet cable Tester		
9	Epson ELPAP10 Wireless Dongle		
	This high-speed, wireless network adapter plugs directly into select Epson projectors allowing quick and easy access to the LAN or peer-to-peer networks without wires or cables. When used with Epson EasyMP Monitor and Network Projection software, users can remotely access and control projectors over the wireless LAN. • Compliant with 802.11 b/g/n standards • Uses USB type A connector • Compatible with PC or Mac • Able to transmit audio		
	• Model: V12H731P02		
10	Fiber Patch panel (LIU Loaded)		
10.1	12 ports		
10.2	24 ports		
10.3	48 port		
11	Switch rack		
11.1	Switch rack 9U		
12	Fiber patch code		
12.1	Single mode, 3M SC-to-LC		
12.2	Single mode, 3M LC-to-LC		
13	R45 Connectors		
13.1	R45 Connectors		
14	UTP cable		
14.1	Cat6e indoor		
14.2	Cat6e outdoor		
14.3	Armored fiber optic cables (in meter)		



15	SFP Module		
15.1	• SFP module, 1.25G, SM 1310nm,		
	• Flexible architecture (Should be compatiable with major brands of switch)		
	Hot-swappable		
	RoHS compliant		
	• Compliant to SFP+ Electrical MSA SFF-8431		
	Compliant to SFF-8472 MSA		
16	Wireless Access Point - Indoor & Outdoor (Unifi or Equivalent)		
16.1	UAP AC PRO		
10.1	PoE Adapter: Yes		
16.2	PoE Adapter for Unifi Indoor AP		
10.2	output of 48V UPOE-af		
17	Switches		
17.1	Core switch (Allied Telesis AT-x230-28GP/Equivalent)		
17.1.1	Managed Switch with 24 x 10/100/1000T PoE ports and 4 x 100/1000X SFP ports		
17.1.1	- 3 years replacement warranty		
17.1.2	Managed Switch with 24 x 10/100/1000T ports and 4 x 100/1000X SFP ports		
	- 3 years replacement warranty		
17.2	Edge Switch (Allied Telesis AT-x230-18GP/Equivalent)		
17.2.1	Managed Switch with 16 x 10/100/1000T PoE ports and 2 x 100/1000X SFP ports		
17.2.1	- 3 years replacement warranty		
17.2.2	Managed Switch with 16 x 10/100/1000T ports and 2 x 100/1000X SFP ports		
	- 3 years replacement warranty		
17.3	Edge Switch (Allied Telesis AT-x230-10GP/Equivalent)		
17.3.1	Managed Switch with 8 x 10/100/1000T PoE ports and 2 x 100/1000X SFP ports		
17.5.1	- 3 years replacement warranty		
17.3.2	Managed Switch with 8 x 10/100/1000T ports and 2 x 100/1000X SFP ports		
	- 3 years replacement warranty		
17.4	Router (Cisco 7200 Series or Equivalent)		specs attached



18	Camera & Microphone (compatible with MAXHUB Interactive Panel)		
10			
10.1	4K USB/HDMI Video Conference System -: Camera, Microphone, and Speaker Bar for Large Conference Rooms - Presenter Tracking, NoiseBlock AI + Echo Cancellation, Intelligent Facial Detection and Auto Framing, 12MP camera with		
18.1	5x digital zoom, Ultra-wide 120-degree field of view, 8 meters clear pickup		
	distance, 25 feet Expansion microphone - Teams/Zoom Certified. System Stand:		
	Yes, 2 years replacement warranty		
19	pfSense hardware		
17	processe naruware		
	• CPU: Intel "Xeon-DE" D-1537, 1.7 GHz FCBGA 1667 supported SoC		
	Standard: Standard 1U rack mount		
	• CPU Cores: 8		
	Memory: 32 GB ECC UDIMM		
	• Storage: 256 GB M.2 SSD		
	• Network Interfaces: Dual LAN via Intel® i350-AM2 1 Gigabit • • Ethernet, Dual		
	LAN via SoC 10GbE SFP+, Virtual Machine • • • Device Queues reduce I/O		
	overhead, Supports		
	10GbE (SFP+), 100BASE-TX, and 1000BASE-T (RJ45), 1x Realtek RTL8201N •PHY (dedicated IPMI)		
	•Network Expansion: 4-Port Intel GbE and 2-port Chelsio SFP+ Expansion		
	•USB Ports: 2x 3.0 ports		
	◆Console Port: VGA		
	Case: Standard 1U rack mount		
	Cooling: Active		
	•License for Software: Free and Open Source Software. No license or subscription		
	fee		
	Warranty Period: Three years		
	●Equivalent to XG-1537 MAX pfSense+ Security Gateway		



Canon ir2525w or Quivalent Specification

MAIN UNIT	garvaiene speemearion
SYSTEM TYPE	Monochrome Digital Multifunction Imaging System
FUNCTIONS	Standard: Copy, Print (UFR II LT), Scan Optional: Print (PCL, PostScript 3 Emulation), Send (Color Send, Searchable PDF), Fax
OPERATION PANEL	5.7" QVGA Black-and-White LCD Touch-Screen
MEMORY	Standard: 512MB RAM Maximum: 512MB RAM
NETWORK INTERFACE CONNECTION	Ethernet 10/100Base-TX
OTHER INTERFACE	Standard: USB 2.0 (Host)x1, USB 2.0 (Device)x1 Optional: USB 2.0 (Host)×3 (USB Application 3-Port Interface Kit-A1), Serial Interface, Copy Control Interface
COPY / PRINT SPEED (BW)	Up to 25 ppm Legal: Up to 13 ppm 11" x 17": Up to 15 ppm
PAPER SOURCES (20 lb. Bond)	Standard: Dual 550-sheet Paper Cassettes 100-sheet Stack Bypass Optional: Dual 550-sheet Paper Cassettes Maximum: 2,300 Sheets
OUTPUT PAPER CAPACITY (20 lb. Bond)	Standard: 250 Sheets (Inner Tray) Maximum: 1,100 Sheets (w/Inner Finisher-B1 and Inner Finisher Additional Tray-B1)
	Cassette 1/3/4: 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive
OUTPUT PAPER SIZES	Cassette 2: 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, Envelopes (COM10 No.10/Monarch/DL/ ISO-B5/ISO-C5)*
	Bypass: 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, Envelopes (COM10 No.10/Monarch/DL/ISO-B5/ ISO-C5), Custom Size (3-15/16" to 11-11/16" x 5-7/8" to 17" [99mm to 297mm x 148mm to 432mm])

ACCEPTABLE PAPER WEIGHTS	Cassettes: 17 lb. Bond to 24 lb. Bond (64 to 90g/m2)	
ACCEPTABLE PAPER WEIGHTS	Bypass: 17 lb. Bond to 34 lb. Bond (64 to 128g/m2)	
SPECIAL MEDIA SUPPORT	Cassette 2: Envelopes	
SPECIAL MEDIA SUPPORT	Bypass: Transparencies, Labels, Envelopes	
WARM-UP TIME	From Power On: 30 Seconds or Less	
WARNI-OF THIL	From Sleep Mode: 1 Second or Less	
POWER REQUIREMENTS	120V AC, 60Hz, 6.9A	
PLUG	NEMA 5-15P	
POWER CONSUMPTION	Maximum: 1,473W; Sleep Mode: 1W	
DIMENSIONS (M/ V D V LI)	35-1/4" x 22-1/4" x 27-1/4" (896mm x 565mm x 693mm) (with DADF)	
DIMENSIONS (W X D X H)	31-3/4" x 22-1/4" x 26-3/4" (806mm x 565mm x 680mm) (with Platen Cover)	
INSTALLATION SPACE (WXD)	42-1/2" x 56-3/4" (1079mm x 1441mm) (with no optional equipment attached)	
INSTALLATION SPACE (WAD)	54" x 56-3/4" (1371mm x 1441mm) (with optional Inner Finisher-B1 attached)	
WEIGHT	Approximately 156 lb. (70.7kg) (Main Unit)**	
WEIGHT	Approximately 172 lb. (78kg) (with DADF)**	
COPY SPECIFICATIONS		
FIRST-COPY-OUT-TIME (Letter)	5.4 Seconds	
MULTIPLE COPIES	1 to 999	
COPY EXPOSURE	Automatic or Manual (9 Levels)	
MAGNIFICATION	25% - 400% (1% Increments)	
PRESET REDUCTIONS	25%, 50%, 64%, 73%, 78%	
PRESET ENLARGEMENTS	121%, 129%, 200%, 400%	
BASIC COPY FEATURES	Preset R/E Ratios by Area, Finishing, Two-sided, Exposure Adjustment, Original Type Selection	
SPEACIAL COPY FEATURES	ID Card Copy, Two-page Separation, Image Combination, Frame Erase, Different Size Original, Sharpness, Mode Memory, Booklet	

PRINT SPECIFICATIONS	
PROCESSOR	Canon Custom Processor (Shared)
MEMORY	Standard: 512MB RAM
INCINOITY	Maximum: 512MB RAM
ENGINE RESOLUTION	1200 x 1200 dpi (Maximum)
PDL SUPPORT	Standard: UFR II LT
1 22 33 1 31 1	Optional: PCL 5e/6, PostScript 3 Emulation
PRINT DRIVERS SUPPORTED OS	UFR II LT, PostScript 3 Emulation: Windows® (Windows 2000/XP/Vista®/Windows 7/Server 2003/Server 2008), Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0, XenDesktop 2.0/2.1/3.0, Macintosh® (OS X 10.6.1), SAP (PS3 Only)
	PCL 5e/6: Windows (Windows 2000/XP/Vista/ Windows 7/Server 2003/Server 2008), Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0, XenDesktop 2.0/2.1/3.0, SAP
PRINT FEATURES	Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Toner Reduction, Poster Printing, Generic PCL 6 Driver
SCAN SPECIFICATIONS	
NETWORK TWAIN SCAN	Standard
NETWORK SCAN UTILITY	Color Network ScanGear
COLOR SEND SPECIFICATIONS	
SENDING METHOD	E-Mail, I-Fax, File Server (FTP, SMB), Super G3 Fax (Optional)
COLOR MODE	Color, BW

SCAN RESOLUTION	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
ADDRESS BOOK CAPACITY	Max. 500 Destinations (Includes 200 One-Touch Buttons)
COMMUICATION PROTOCOL	File: FTP (TCP/IP), SMB (TCP/IP)
	E-Mail/I-Fax: SMTP, POP3, I-Fax (Simple)
FILE FORMAT	TIFF, JPEG, PDF, PDF (Compact), PDF (OCR)***
I-FAX DATA FORMAT	TIFF (MH)
FAX SPECIFICATIONS (Standard on "iF"	
models, optional for Base models)	
NUMBER OF CONNECTION LINES	1 (Maximum)
MODEM SPEED	Super G3: 33.6 Kbps
MODEM SPEED	G3: 14.4 Kbps
COMPRESSIONS METHOD	MH, MR, MMR, JBIG
RESOLUTION	400 x 400, 200 x 400, 200 x 200, 200 x 100
SENDING / RECORDING SIZE	Statement-R to 11" x 17"
FAX FEATURES	Job Forwarding, Different Size Originals, Sharpness, Delayed Send, Finished Stamp, Two-sided Original
SECURITY SPECIFICATIONS	
	ment, IPv6, Restricting Features (Restricting the Send Function, Restricting
1 '	ok Password, Allow Fax Driver TX, Restrict Recall, Confirm Entered Fax
· ·	MPv1, MAC/IP Address Filtering, SMTP Authentication, POP Authentication
before SMTP	ii vi, iii totii 7taarooo i iitoriiig, oiviii 7taaronaoaaon, i or 7taaronaoaaon
BOISTO CIVITI	
ENVIRONMENTAL INFORMATION	
ENERGY STAR® Qualified	
RoHS Compliant	†
Ecomark	†
Blue Angel	1
WEEE Directive	1

CONSUMABLES	
TONER	GPR-35 Toner
TONER YIELD (ESTIMATED @ 6% COVERAGE)	14,600 Copies/Bottle

Router Specifications

Network interface modules (NIM)	3
Maximum switched Ethernet LAN ports with PoE	48
EtherSwitch Service Module type (width)	2 single or 1 double
PoE support (wattage) without PoE boost	500 W (with optional power supply redundancy)
Intrusion prevention	Yes
Cisco Cloud Web Security	Yes
Form factor	2 RU
SSL VPN	No
Module online insertion and removal (OIR)	Yes
Power supply type	Internal; AC, PoE or DC
Maximum switched Ethernet ports	48
Hardware VPN acceleration (DES, 3DES, AES)	No
Redundant power supply	Yes - Internal RPS
Management port	1 GE (Integated Out of Band)
PoE support (wattage) with PoE boost	950 W (no power supply redundancy)
Integrated Services Card (ISC) slots	1 (PVDM 4)
	2-core single-wide, 4-core single-wide, 4-core double-wide, 6-core double-wide, 8-core
Server virtualization platform (UCS E-Series)	double-wide
Enhanced Services Module (SM-X)	2 single or 1 double-wide
Identity-based networking	No
Zone-based fiewall and NAT services	VRF-Aware Firewall and Network Address Translation (NAT)
USB Ports (type A)	2
Integrated WAN ports	2 PoE GE / SFP; 2 GE / SFP
Default/max DRAM	4 GB / 16 GB
Default/max Flash	8 GB / 32 GB
Performance	1 Gbps upgradeable to 2 Gbps